

### **1. INITIAL CLEANING**



a. Remove loose dirt using a broom or a vacuum cleaner.



**b**. Apply uniformly an INTENSIVE CLEANER according to the manufacturer's instructions using a washing cotton string mop.



**c**. Let the solution soak for about 3 to 5 minutes without allowing to dry, then clean. Use a single-disc, low speed (150-200 RPM) cleaning machine with red pad or soft brush (semi-hard bristles). If a cleaning machine is not available, use a suitable broom or brush to manually clean the floor.



**d**. Remove the solution using an acqua-vacuum cleaner or wash string mop. Rinse thoroughly with clean water to completely eliminate any dirt residue.



#### 2. INITIAL PROTECTION / CARE



a. Use a rayon string mop or waxing mop pad to apply the recommended protective emulsion according to the manufacturer's instructions.



**b**. If required, polish with white pad or soft brush.

**Note:** On electrically conductive floorcoverings, do not use emulsions that may adversely affect the electric properties of the floorcovering.

**Important:** Failure to comply with the initial cleaning and / or protection processes may hinder the subsequent cleanings.



### **3. REGULAR MAINTENANCE / CLEANING**



a.Remove loose dirt using a broom or a vacuum cleaner.



**b**. Apply uniformly a BASIC CLEANER according to the manufacturer's instructions using a cotton string washing mop.



**c**. Let the solution soak for about 3 to 5 minutes without allowing to dry, then clean. Use a single-disc, low speed (150-200 RPM) cleaning machine with red pad or soft brush (semi-hard bristles). If a cleaning machine is not available, use a suitable soft bristle broom or brush to manually clean the floor. The choice of pad (red or white) or brush type (semi hard or soft bristles) depends on the quantity of accumulated dirt on the floor.





**d**. Remove the solution using an acqua-vacuum cleaner or wash string mop.



**e**. If necessary polish the remnant protective emulsion with white pad or soft brush.

#### **4. PERIODIC CLEANING**

**a**. When the floorcovering image begins to decline due to accumulating layers of dirty emulsion, repeat the INITIAL CLEANING process using an INTENSIVE CLEANER to remove all the protective emulsion. Then perform the INITIAL CARE/PROTECTION process.

#### **5. IMPORTANT NOTES**

- **a**. We recommend to closely follow the instructions given by Indelval SAIC for the maintenance of their floorcoverings, unless special instructions are provided by the company for specific cases.
- **b**. It is recommended to use large mats in all the entrance areas to trap loose dirt.
- c. Do not use cleaning products with a pH-value above 12, unless so indicated by Indelval SAIC.
- d.Never use grit brushes or brown/black pads.
- e. On studded floorcoverings always use brushes instead of pads.
- f. Never use petroleum derivated cleaners or waxes (naphthas, solvents, acetones, etc.).
- g.Do not use color waxes.
- **h**. For cleanings in specific areas such as health centres, raised floorings or sports floorcoverings, or regarding any further questions or queries you may have about the cleaning and maintenance of our rubber floorcoverings, please contact us.







rubber flooring

#### **CLEANING WITH PROFESSIONAL PRODUCTS – RECOMMENDED CLEANING AGENTS**

The cleaning agents mentioned are recommended for the Argentine domestic market. The product information available to other countries may be requested from Indelval SAIC Technical Department or the respective local representative. While there may be other products on the market that may be suitable for maintenance, they have not been tested by Indelval SAIC. For more information visit www.indelval.com

Supplier	Initial Cleaning	Initial Protection	Regular Cleaning
	Intensive Cleaner	Protective Emulsion	Basic Cleaner
Sutter Argentina Cerrito 1294, Piso 17 C1010AAX Bs. As., Argentina (54-11) 4816-3332 (54-11) 4816-3338	<b>Strip 83</b> Removes emulsions. 8% to 12% water diluted. Rinse.	<b>PB 28</b> Apply twice undiluted.	<b>Fresco</b> Dilute 200-400 g in 8-10 litres of water.
JohnsonDiversey de Argentina S.A. Av. Márquez 970 B1682BAQ - Villa Bosch Bs. As., Argentina (54-11) 4842-8200 0810-HIGIENE	<b>Emerel Forte</b> Removes emulsions. Apply 1:5 diluted with water. Rinse. With automatic washing machine use an anti-foam agent.	<b>8M</b> Apply twice undiluted.	<b>Stride</b> Apply 1:35 for manual cleaning. Apply 1:60 for machine cleaning.
	<b>Pro Strip</b> Removes emulsions. Apply 1:5 diluted with water. Rinse.	<b>Signature</b> Apply twice undiluted.	

NOTE: Cleaning with professional products should always take place with adequate equipment.